



**Note:** Information contained herein has been collected from container manufacturers and other sources. CAL will be under no liability of any kind whatsoever by reason of any inaccuracy contained in this information. All containers have the usual Industry Certifications.




	Standard 20'		Upgraded 20'		Standard 40'		High Cube 40'	
Inside length	19'4"	5.89 m	19'4"	5.89 m	39'5"	12.01 m	39'5"	12.01 m
Inside Width	7' 8"	2.33 m	7' 7"	2.31 m	7' 8"	2.33 m	7' 8"	2.33 m
Inside Height	7' 10"	2.38 m	7' 10"	2.38 m	7' 10"	2.38 m	8' 10"	2.69 m
Door Width	7' 8"	2.33 m	7' 6"	2.28 m	7' 8"	2.33 m	7' 8"	2.33 m
Door Height	7' 6"	2.28 m	7' 6"	2.28 m	7' 6"	2.28 m	8' 5"	2.56 m
Capacity	1,172 cft	33.18 m3	1,150 cft	32.56 m3	2,390 cft	67.67 m3	2,694 cft	76.28 m3
Tare Weight	4,916 Lbs.	2,229 Kgs.	5,060 Lbs.	2,295 Kgs.	8,160 Lbs.	3,701 Kgs.	8,750 Lbs.	3,968 Kgs.
Max. Cargo	47,999 Lbs.	21,727 Kgs.	61,993 Lbs.	28,120 Kgs.	59,040 Lbs.	26,780 Kgs.	58,450 Lbs.	26,512 Kgs.




	Reefer 20'		Reefer 40'		Reefer High Cube 40'	
Inside length	17' 8"	5.38 m	37' 8"	11.48 m	37' 11"	11.35 m
Inside Width	7' 5"	2.26 m	7' 5"	2.26 m	7' 6"	2.28 m
Inside Height	7' 5"	2.26 m	7' 2"	2.18 m	8' 2"	2.48 m
Door Width	7' 5"	2.26 m	7' 5"	2.26 m	7' 6"	2.28 m
Door Height	7' 3"	2.20 m	7' 0"	2.13 m	8' 0"	2.43 m
Capacity	1,000 cft	28.31 m3	2,040 cft	57.76 m3	2,344 cft	66.37 m3
Tare Weight	7,040 Lbs.	3,193 Kgs.	10,780 Lbs.	4,889 Kgs.	9,900 Lbs.	4,490 Kgs.
Max. Cargo	45,760 Lbs.	20,756 Kgs.	56,276 Lbs.	25,526 Kgs.	57,561 Lbs.	26,109 Kgs.


## EQUIPMENT SPECIFICATIONS




	Open Top 20'		Open Top 40'	
Inside length	19' 4"	5.89 m	39' 5"	12.01 m
Inside Width	7' 7"	2.31 m	7' 8"	2.33 m
Inside Height	7' 8"	2.33 m	7' 8"	2.33 m
Door Width	7' 6"	2.28 m	7' 8"	2.33 m
Door Height	7' 2"	2.18 m	7' 5"	2.26 m
Capacity	1,136 cft	32.16 m <sup>3</sup>	2,350 cft	66.54 m <sup>3</sup>
Tare Weight	5,280 Lbs.	2,394 Kgs.	8,490 Lbs.	3,850 Kgs.
Max. Cargo	47,620 Lbs.	21,600 Kgs.	58,710 Lbs.	26,630 Kgs.




	Flat Rack 20'		Flat Rack 40'	
Inside length	18' 5"	5.61 m	39' 7"	12.06 m
Inside Width	7' 3"	2.228 m	7' 3"	2.228 m
Inside Height	7' 4"	2.233 m	7' 4"	2.233 m
Tare Weight	5,578 Lbs.	2,530 Kgs.	12,081 Lbs.	5,479 Kgs.
Max. Cargo	61,117 Lbs.	27,722 Kgs.	85,800 Lbs.	38,918 Kgs.



	Flat Rack Collapsible 20'		Flat Rack Collapsible 40'	
Inside length	18' 6"	5.63 m	39' 7"	12.06 m
Inside Width	7' 3"	2.228 m	7' 3"	2.228 m
Inside Height	7' 4"	2.233 m	7' 4"	2.233 m
Tare Weight	6,061 Lbs.	2,749 Kgs.	12,787 Lbs.	5,800 Kgs.
Max. Cargo	61,117 Lbs.	27,722 Kgs.	85,800 Lbs.	38,918 Kgs.



	Platform 20'		Platform 40'	
Inside length	19' 11"	6.07 m	40' 0"	12.19 m
Inside Width	8' 0"	2.43 m	8' 0"	2.43 m
Inside Height	7' 4"	2.23 m	6' 5"	1.95 m
Tare Weight	6,061 Lbs.	2,749 Kgs.	12,783 Lbs.	5,798 Kgs.
Max. Cargo	52,896 Lbs.	23,993 Kgs.	66,397 Lbs.	30,117 Kgs.



	Chassis 23' 6"		Chassis 33' Tri-Axle		Chassis 40' Gooseneck	
Length						
overall extended	27' 6"	8.25 m	41' 3"	12.37 m	40'	12 m
Tare Weight	6,500 Lbs.	2,954 Kgs.	10,900 Lbs.	4,954 Kgs.	6,500 Lbs.	2,954 Kgs.
Max. Cargo	39,500 Lbs.	17,955 Kgs.	44,500 Lbs.	20,227 Kgs.	44,500 Lbs.	20,227 Kgs.
Overall unextended			33' 3"	9.97 m		
Tare weight			10,900 Lbs.	4,954 Kgs.		
Max. Cargo			39,500 Lbs.	17,955 Kgs.		